

U 923B 音频总线收发器测试仪 产品规格书

U 923B Audio Bus Transceiver Tester Product Specifications

产品规格书-中文	1
Product Introduction-EN.....	3

最终版权所有 (c) 深圳市美格信测控技术有限公司

Copyright (c) Shenzhen MegaSig Measurement & Control Technology Company Limited

从此文件发布日期起，在此发表的是当前或者拟定的信息。由于我们会不断对产品进行改进和增加特征此出版物中的信息如有变动恕不另行通知。

The information presented herein reflects the current or intended specifications as of the date of publication. As we continuously improve our products and add new features, the contents of this publication are subject to change without prior notice.

产品简介



U 923B A2B 音频总线收发器测试仪

U 923B 是基于目前新兴音频总线A2B 测试的分析解决方案。A2B 技术的确定性使其合适在远距离的音频场景使用，结合软件工具可以高效的进行各种 A2B 部件的测试，比如扬声器，音频放大器，麦克风阵列，传感器及驱动器。

可选作为主或从节点进行仿真

U 923B 支持多种接口，拥有内部TDM、外部音频接口 S/PDIF和3.5mm Analog接口，适用于研发和量产测试。

产品参数

U 923B 参数	
驱动	Shuttle
A2B 接口	工业级连接器
通讯控制	USB
工作电压	12V
外部接口类型	S/PDIF 、 Analog
输出至从节点电压	5V-8V拨码开关可调
尺寸(mm)	96*33*140（W x H x D）
适用温度	-20°C~50°C
芯片型号	AD2433

基本特点

- 兼容 AD240x, AD241x, AD242x及243x系列收发器
- 支持内部TDM接口可调，兼容性强，可生成各类型测试信号，支持WAV等
- 可作为主节点仿真，或者从节点仿真
- 支持3.5mm模拟输入输出接口
- 支持S/PDIF输入输出接口
- 输出至从节点电压5V-8V可调
- 通过AD Sigma Studio可快速配置A2B网络
- 无缝支持Audio Expert和SIO LAB，可对节点信号进行快速分析，例如频响、幅值、THD+N等

在无深圳市美格信测控技术有限公司优先书面授权书前提下，此出版物任何一个部分不可通过任何形式进行 复制、修改和翻译。对于非法复制、修改和翻译商业行为，将根据国家知识产权相关法律追求其法律责任。



深圳市美格信测控技术有限公司

电话：0755-8950.8393

传真：0755-8950.8392

销售邮箱：sale@megasig.com

技术支持：support@megasig.com

地址：中国.深圳.光明.光明数字智造产业园1栋2单元4楼5楼

版本号：V2.2_20260528_CN

Product introduction



U 923B A2B Audio Bus Transceiver Tester

U 923B is an analysis solution based on the currently emerging audio bus A2B testing. The deterministic nature of A2B technology makes it suitable for use in long-distance audio scenarios. Combined with software tools, it can efficiently test various A2B components, such as speakers, audio amplifiers, microphone arrays, sensors and drivers.

It can be selected as a master or slave node for simulation.

U 923B supports multiple interfaces, featuring an internal TDM interface, an external audio interface S/PDIF, and a 3.5mm Analog interface, making it suitable for both R&D and mass production testing.

Specifications

U 923B Parameter	
Driver	Shuttle
A2B interface	Industrial-grade connector
Communication control	USB
Operating voltage	12V
External interface type	S/PDIF 、 Analog
Output voltage to slave node	5V-8V Dip switch is adjustable
Dimension(mm)	96*33*140 (W x H x D)
Operating Temperature	-20°C~50°C
Chip model	AD2433

Basic features

- Compatible with AD240x, AD241x, AD242x and 243x series transceivers
- Supports adjustable internal TDM interface, high compatibility, can generate various types of test signals, supporting WAV and more
- It can be configured to emulate a master or a slave node
- Supports 3.5mm analog input/output interfaces
- Supports S/PDIF input/output interfaces
- Output adjustable slave node voltage ranging from 5V to 8V
- A2B network can be rapidly configured via AD Sigma Studio
- Seamlessly supports Audio Expert and SIO LAB, enabling rapid analysis of node signals for metrics, such as frequency response, amplitude, and THD+N

Without the prior written authorization of Shenzhen MegaSig Measurement & Control Technology Company Limited, no part of this publication may be reproduced, modified or translated in any form. Legal liability will be pursued in accordance with the national laws on intellectual property rights for commercial activities involving illegal reproduction, modification or translation.



www.megasig.com

**MegaSig Measurement & Control Technology
Company Limited**

Tel: 0755-8950.8393

Fax: 0755-8950.8392

Sales email: sale@megasig.com

Technical support email: support@megasig.com

Address: 4th & 5th floors, Unit 2, Building 1, Guangming
Digital Smart Manufacturing Industrial Park, Jinmo Road,
Guangming District, Shenzhen, China

Version number: V2.2_20260528_EN