

BNC plug to BNC plug low noise cable 102A

Version: 2.1_20260603_EN



BNC plug to BNC plug low noise cable, specially designed for audio systems, with a characteristic impedance of 50 ohms. The cable features a pure nickel wire core for stable transmission, with an outer diameter of 1.9mm and made of blue PFA material. It has a fine wire diameter and high wear resistance.

This cable is widely used in audio testing systems, connecting amplifiers, speakers, sensors, and other devices.

Product Characteristics

- Complies with UL1581/2000 engineering design reference standard & UL758/2000 testing standard.
- Complies with ROHS & REACH environmental protection testing standards.
- The cable can withstand a maximum temperature of 250°C.
- Noise level (pk - pk) ≤5mv.


Product Technical Parameters

Cable Length	1.5m、 3m、 6m、 9m、 12m, custom cable length
Temperature Range	-60℃~250℃
Impedance	50Ω
Connector Type	BNC Plug to BNC Plug
Strain Relief	PVC molded boot
Cable Specifications	Coaxial cable, Inner core of pure nickel wire + PFA insulation + isolation layer + Braided high shielding ≥ 95% Cable jacket: Blue PFA-OD:1.9mm±0.05mm

Ordering Information

Optional parameter length	
102A	BNC Plug to BNC Plug,cable jacket diameter 1.9mm,blue PFA low noise cable,high temperature resistance 250℃, Customizable length
102A015	BNC Plug to BNC Plug,cable jacket diameter 1.9mm,blue PFA low noise cable,high temperature resistance 250℃, length 1.5m
102A030	BNC Plug to BNC Plug,cable jacket diameter 1.9mm,blue PFA low noise cable,high temperature resistance 250℃, length 3.0m
102A060	BNC Plug to BNC Plug,cable jacket diameter 1.9mm,blue PFA low noise cable,high temperature resistance 250℃, length 6.0m
102A090	BNC Plug to BNC Plug,cable jacket diameter 1.9mm,blue PFA low noise cable,high temperature resistance 250℃, length 9.0m
102A120	BNC Plug to BNC Plug,cable jacket diameter 1.9mm,blue PFA low noise cable,high temperature resistance 250℃, length 12.0m

External Dimensions



MegaSig reserves the right to change specifications and accessories without notice.



www.megasig.com

MegaSig Measurement & Control Technology Co.,Ltd

Tel: 0755-8950.8393

Fax: 0755-8950.8392

Sales email: sale@megasig.com

Technical support email: support@megasig.com

Address: 4th & 5th floors, Unit 2, Building 1, Guangming Digital Smart Manufacturing Industrial Park, Jinmo Road, Guangming District, Shenzhen, China