

U 987Q 蓝牙适配器

产品规格书

U 987Q Bluetooth dongle

Product Specification

产品规格书-中文.....	1
Product introduction-EN.....	3

从此文件发布日期起，在此发表的是当前或者拟定的信息。由于我们会不断对产品进行改进和增加特征此出版物中的信息如有变动恕不另行通知。

From the date of this document's release, the information published here is current or proposed. As we will continuously improve and add features to our products, the information in this publication is subject to change without further notice.

产品简介



U 987Q 蓝牙适配器

支持 A2DP, HFP (窄带, 宽带, APTX超宽带)

支持 SBC, AAC, APTX, APTX-HD, APTX-Adaptive, LDAC, LHDC-V5

支持 SPP 大数据无断点透传, 极其适用于 ANC 滤波器调试数据传输

支持 RSSI, 电量等信息传输

支持上下曲, 音量, 暂停/回答, 和其他按键的测试反馈

支持录音, 重放, 听音等测试反馈

支持 USB 程控, 专为自动化测试设计

支持 LE Audio, LC3编码(语音, 媒体)。Auracast发射

功能特点

- 支持蓝牙 5.4
- 具有完整的配置接口
- 完可设置音频编码
- 完整的音频 Profile 支持
- SPP高速大包透传
- 扫码连接, 盲扫连接
- 模拟, USB声卡和数字(i2s)接口支持输入输出

规格参数

整体参数	
驱动	Shuttle
工作电压/电流	5V/55mA
尺寸	93*33*140
适用温度	-20°C - 50°C
蓝牙指令控制	USB
Speaker通道数	2
Mic通道数	1
接口类型	BNC,USB

音频特性参数

音频参数	
Profile 版本	A2DP v1.4/AVRCP v1.6/HFP v1.8
RF 工作频率	2.441GHz
RF 射频功率	最大典型值 +15 dBm
A2DP 音频编解码	SBC/AAC/APTX/APTX-HD/APTX-Adaptive/LDAC/LHDC-V5
HFP 音频编解码	CVSD/mSBC/APTX Voice
LE AUDIO媒体编码	LC3（帧长支持10ms与7.5ms）
LE AUDIO语音编码	LC3（支持SWB）
Speaker 带宽	20Hz – 41kHz
Mic 带宽	100Hz – 15kHz
Speaker 底噪	<-90dBV
Mic 底噪	<-90dBV

在无深圳市美格信测控技术有限公司优先书面授权书前提下，此出版物任何一个部分不可通过任何形式进行复制、修改和翻译。对于非法复制、修改和翻译商业行为，将根据国家知识产权相关法律追求其法律责任。

Product introduction



U 987 Bluetooth dongle

Support A2DP, HFP (Narrowband, Wideband, APTX ultra-wideband)

Support SBC, AAC, aptX, APTX-HD, APTX-Adaptive, LDAC, LHDC-V5

Support SPP high speed, ideally for ANC filter data transmission Support RSSI, Power and other information upload

Support up and down, volume, pause / answer, and other key feedback Support recording, replaying, listening key feedback

Support USB program control for automated test design

Supports LE Audio and LC3 encoding (voice, media). Auracast broadcasting

Features

- Supports Bluetooth 5.4
- The audio codecs can be set
- With a complete function of the configuration interface
- Full audio profile support
- SPP high speed transmission capability
- RF transmitter power can be set
- Connect by mac address or auto connect BT device
- Analog, USB sound card and digital (i2s) interface support inputs and outputs

Specification parameters

Parameters	
Driver	Shuttle
Working voltage/power dissipation	5V/55mA
Dimensions(mm)	93*33*140
Operation temperature	-20°C - 50°C
Bluetooth command control	USB
Speaker channel number	2
Mic channel number	1
Interface type	BNC,USB

Audio specifications

Audio parameters	
Profile versions	A2DP v1.4/AVRCP v1.6/HFP v1.8
Rf frequency	2.441GHz
RF power	Typical max +15 dBm
A2DP audio codecs	SBC/AAC/APTX/APTX-HD/APTX-Adaptive/LDAC
HFP audio codecs	CVSD/mSBC/APTX Voice
LE AUDIO media codec	LC3 (supports frame lengths of 10ms and 7.5ms)
LE AUDIO voice codec	LC3 (supports SWB)
Speaker bandwidth	20Hz - 41kHz
Mic bandwidth	100Hz - 15kHz
Speaker noise	<-90dBV
Mic noise	<-90dBV

Without the prior written authorization of Shenzhen MegaSig Measurement And Control Technology CO LTD., no part of this publication may be reproduced, modified or translated in any form. Legal liability will be pursued in accordance with the national laws on intellectual property rights for commercial activities involving illegal reproduction, modification or translation.