

# **PR 0X Series Audiometry Kit**



The PR OX series of products is specifically designed for subjective evaluations of hearable devices. The internal microphone and ear canal are modeled to simulate human hearing. With a system rated power of  $100mw@320\Omega$  and powered by a USB Type-C port, there is a 3.5mm port located on the backside of the product that enables real-time monitoring when connected to an earphone.

Bundled with the PM 0095, up to 5 PR OX series products can be connected in series, offering flexible testing and monitoring capabilities by allowing users to switch between them.

#### **Product Feature**

- The unique design aims to replicate the performance of human hearing as closely as possible.
- Custom made microphone and ear canal design for real hearing perception.
- The 3.5mm port interface allows for real-time listening when connected to an earphone or headphone.
- Products output volume is adjustable.

#### **General Specification Parameter**

Signal output interface	3.5mm interface, four core interface
Output power	100mW@32Ω
Power supply interface	Туре С
Power supply	5W
Threaded connection port	1/4 inch thread
Product size (single product)	195*95*95 (mm)
Weight (single product)	730g

#### **Specifications of Each Type**


	PR 02	PR 03
THD@1KHz	< 3% at 125dB	< 3% at 110dB
SNR	66dB	76dB




Equips engineers to create better products


Frequency Range	20Hz-20kHz	20Hz-20kHz
Sensitivity	-40.0dB ± 1dB re 1V/Pa	-30.0dB ± 1dB re 1V/Pa
Application Example	Audiphone	Bluetooth headset, Wired headset, ASMR Record


### **Correlation Curve**













Equips engineers to create better products

## **Product Picture**









Main part			
Serial number	Product picture	Contents	Quantity
	MagaSig Market MagaSig	PR 02 (Including ER 66L and ER 66R ears)	1
		Round/square base bracket	1
		3.5mm audio cable * 1m	1
000055 00		Charging cable	1
990055-02		Double end 1/4-20 UNC threaded connection ( adjustable )	1
		Double end 1/4-20 UNC threaded connection (Non adjustable )	1
		1/4-20 UNC thread extension	2
990055-03	CogaSig Dur O prost	PR 03 (Including ER 66L and ER 66R ears)	1
		Round/square base bracket	1
		3.5mm audio cable * 1m	1
		Charging cable	1
		Double end 1/4-20 UNC threaded connection ( adjustable )	1
		Double end 1/4-20 UNC threaded connection (Non adjustable )	1
		1/4-20 UNC thread extension	2

Multiple signal cable			
Serial number	Product picture	Contents	Quantity
720004-06		Three to three -M8, four core connection cable	1
720004-07		Four to four -M8, four core connection cable	1
720004-08		Five to five -M8, four core connection cable	1

Switches			
Serial number	Product picture	Contents	Quantity
910023-02		PM 0095 Signal control switch box (Can support five Product same time to work.)	1